



Harmony LSA is aerodynamically controlled, single-engine, two-seated, low-wing plane with a fixed tricycle undercarriage. The airframe is combination of an advanced metal airframe, riveted and bonded for enhanced durability, and composites parts to achieve elegant external contours. The model is based on a successful aircraft SportStar.

The plane meets ASTM Consensus Standards and FAA Sport Pilot rule.

1. GENERAL DESCRIPTION OF THE PLANE

1.1. Fuselage

The fuselage has a semimonocoque construction formed with reinforcements and duralumin skins. The fuselage cross-section is rectangular in the lower section, elliptical in the upper one. The tail fin is an integral part of the fuselage. In the middle section of the fuselage there is a two-man crew cockpit accessible after unfolding the one-part perspex overlap canopy. The engine section is separated from the crew by a firewall in the nose, which the engine bed is attached to.

1.2. Wing

The rectangular wing is a monospar construction with an auxiliary spar for the ailerons and flaps attachments. All the elements are riveted together. At the ends of the wings are riveted fiberglass wing tips.

1.3. Horizontal tail unit (HTU)

The HTU consists of a stabilizer and elevator with a trim tab. The semimonocoque construction of the HTU consists of duralumin ribs, spar and skin. The shape of the HTU is rectangular. The width of 2.5 m (8.22 ft) enables transport on a trailer without dismantling.

1.4. Vertical tail unit (VTU)

The VTU has a trapezoidal shape. Its fin part is an integral part of the fuselage rear. The rudder is attached to the fin part by two hinges. The construction of the VTU is composed of a metal sheet spar and a duralumin skin.

1.5. Landing gear

The plane has a fixed undercarriage with steerable nose wheel. The main undercarriage legs are made from composite springs. The wheels on both undercarriage legs are equipped with 15 x 6 tires and with hydraulic disc brakes, controlled by toe brake pedals on the rudder pedals. Main wheels have external brake caliper for easy and fast brake pads replacement. The undercarriage leg of the nose wheel is made from steel. The nose landing gear is spring-loaded by rubber blocks. The nose wheel is controllable, wheel control is coupled with rudder control by means of two pull rods.

1.6. Control

The plane is equipped with a classic dual control system. The ailerons and elevator are controlled by control sticks, connecting push-pull rods and bell cranks. The rudder is controlled by pedals and cables. Adjustment of rudder pedals position is made through pedal adjustment system with levers located at bottom of instrument board. There are anti-skid bands on the pedals.

The flaps are controlled mechanically; the flaps control lever is located between the seats. The elevator trim tab is standardly mechanical, operated by a trim control lever located between the seats. Longitudinal as well as lateral electric trims with dual control switches and LED light indicators are on request.

1.7. Power plant

Standard power plant consists of Rotax 912 ULS (100 HP) engine and a composite ground adjustable propeller Propuls AES 1700/3/R with a conical spinner. Rotax 912 is a four-cylinder, four-stroke horizontally opposed engine with a central camshaft and OHV distribution. The engine is attached to the engine bed suspended on the firewall. Engine cooling is combined, the cylinder heads are liquid cooled, and the cylinders are air-cooled. Dry sump forced lubrication. Two spark electronic ignition. The engine is equipped with an electric starter, an AC generator and a mechanic fuel pump. An integrated reduction gear box through which a propeller is driven has a gear ratio 2.43 for the 100 HP version. Installation of Rotax 914UL Turbocharged, Rotax 912iS Sport Fuel Injected and other propellers is an option.

1.8. Fuel system

Fuel system consists of two wing integral tanks in total amount 120 liters (31 USgal), a fuel tank selector, a filter and a fuel pump on the engine. Each tank has a sump and drain valve. The fuel tank venting outlet is under the wing tips.

1.9. Electric system

Electric system is single-wire type with the negative connected to the chassis. As a power source serve the single-phase generator integrated to the engine and the 12V maintenance less battery located on the firewall. The system is protected by the main circuit breaker positioned on the instrument panel. Circuit breakers guard the circuits of the particular sections separately.

1.10 Seats and seatbelts

The plane has two side-by-side seats, which are fixed, upholstered, each equipped with four-point safety belts. Shoulder harnesses are attached to the sides for easier access to the luggage compartment with upholstered arm supports.

1.11 Baggage compartment

Behind the backrests located baggage compartment is designed for maximum 25 kg (55 lbs) load.

1.12 Cockpit canopy (wide, light brown tinted)

The plane has a new composite sturdy tip-up canopy. Canopy shape is aerodynamically optimized to reduce drag. Cockpit is roomy and light. The canopy is attached to the nose section of the fuselage by two pins, on which it may be tilted forward. For easier manipulation, the weight of the canopy is counterbalanced by two gas struts, which allow it to open effortlessly. On the lower frame there are handles outside the canopy. The canopy is equipped with a sturdy automotive type latch with open canopy indication. Efficient cockpit ventilation through eye-ball vents is connected to the NACA scoops. Advanced cockpit heating system has a separate regulation of warm and cold air volume and air distribution inside the cockpit, with windshield and canopy side air blowing, defrost and demist system. Handles in dashboard cover enables easier disembarkation.

1.13 Pitot-static system

The Pitot-static head to read air pressure is located under the left wing. Pressure distribution to individual instruments is done through flexible plastic hoses.

1.14 Painting versions

Standard versions: one color only (white), 3x registration marks (foil), 2x Harmony LSA logo (foil), 2x Evektor logo.

Other versions are defined in paint catalogue. Special customer design can be ordered separately.

1.15 Standard aircraft specification

ENGINE INSTRUMENTS	FLIGHT INSTRUMENTS
RPM indicator	Air speed indicator (knots or km/h)
Cylinder head temperature indicator (°C or °F)	Altimeter (feet)
Electric fuel indicator	Magnetic compass
Oil temperature indicator (°C or °F)	Vertical speed indicator (ft / min or m/s)
Oil pressure indicator (MPa or psi)	Bank indicator

CONTROLS	FIREWALL FORWARD
Dual hydraulic brakes (4 pumps)	Propeller Woodcomp Propuls AES 1700/3/R, composite, ground adjustable, spinner
Dual control sticks	Rotax 912 ULS2 (100 HP inclusive slip clutch)
Mechanical flaps + Mechanical elevator trim	12 V battery
Throttle control with friction lock	Exhaust system
Adjustable pedals with remote control lever	Combined engine cooling
New design of instrument panel	Dry sump forced lubrication
Press-button circuit breaker	Two spark electronic ignition system
Nose wheel steering	Electric starter
Combined starting switch	AC generator
Choke lever	Engine oil check cap

INTERIOR	EXTERIOR
Ventilation system with eye-ball vents	Advanced all metal anodized and corrosion-proofed airframe
12 volt auxiliary outlet	All joints of construction riveted as well as bonded for long service life
Four points safety points-belts (with padded shoulder straps)	All heads of pop rivets filled with mastic for longevity of riveted joints
Deluxe lined interior and upholstery seats	Painting (white color only)
Arm rests, side map pockets	Main and nose tires 15x6.00-6
Aft baggage compartment with luggage nets	Tricycle landing gear with steerable nose wheel
Wide aft baggage space	Tinted canopy with automotive type latching mechanism and separate canopy lock
Open/closed canopy alert	Integral wing tanks 120 l (2 x 60 l)

ACCESSORIES
Pilot operating handbook
Maintenance manual
Log book
Ground equipment inclusive canopy cover
Set of aircraft test records

NOTE: For information on optional equipment see Harmony LSA list of options.

2. TECHNICAL SPECIFICATION

Wing span	9,25 m	30 ft 4"
Length	6.11 m	20 ft ½"
Cabin width	1.18 m	46 ½"
Height	2.48 m	8 ft 2"
Basic empty weight	320 kg	705 lb
Useful load	280 kg	615 lb

MTOW	600 kg	1320 lb
Load factors (Ultimate)	+6g / -3g	
Glide ratio	1:10	
Baggage capacity	25 kg	55 lb
Fuel tank capacity	120 l	31,7 USgal

3. PERFORMANCES

Engine	Rotax 912 ULS (100 HP)	
Never exceed speed V_{ne}	270 km/h	146 KIAS
Maximum speed	222 km/h	120 KCAS
Cruising speed at 75% engine power	173 km/h	93 KCAS
Stall speed no flaps v_{s1}	83 km/h	45 KCAS
Stall speed with flaps v_{s0}	74 km/h	40 KCAS
Rate of climb v_z	5,2 m/s	1.020 ft/min
Service ceiling	4720 m	15,500 ft
Take-off run (concrete RWY)	190 m	620 ft
Landing run	180 m	590 ft
Average fuel consumption	15 l/h	4.0 USgal/h
Range no reserve	1300 km	700 NM
Endurance no reserve	8:30 h	

All information in this document may change without prior notice.

EVEKTOR – AEROTECHNIK a.s.
tel. : +420 572 537 111
fax: +420 572 537 910
e-mail: sales@evektor.com
<http://www.evektoraircraft.com>